| | CUSTOMER D | |
|--|---|---|
| Central Article Code: | C38004D03-A | Transportation Europe Created: 02/09/2005 |
| | | |
| Local Code: | 12N5-3B | Modified: 15/12/2020 |
| | 130±2 | |
| | 95.2±0.5 120±2 130±2 | Final Outlook C3803-A Approval date 15/03/2010 |
| PER | FORMANCES | CONTAINER |
| Voltage (V): | 12 V | Type: C38 WHITE |
| C20 (Ah): | 5.0 10 h | Hold Down: B0 |
| Cranking (A): | 40 EN | H.D. Adapter: No |
| Charge: | DRY | COVER |
| Technology: | Vented/Flooded | Type: Motorbike (B ventilati BLACK |
| Grid: | Low Sb | Polarity: ETN 0 |
| Vibration: | Not Defined | Terminals: M06 |
| Endurance: | Not Defined | Terminal Adapter: No |
| | | SOCI: No |
| | | Ventilation: Moto-B |
| STD. DIMENSIONS | | Filter: No |
| Length (mm \pm 2): | 120 | Lateral Plug: No |
| Width (mm \pm 2): | 60 | PLUGS |
| Height (mm ± 2): | 130 | Type: 6 x Moto Plug RED |
| Total Weight (kg ± 5%): | 2.00 | HANDLES |
| | | Type: None |
| | | OTHERS |
| This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users All figures show nominal values. Tolerances are according to EN50342 | | Degassing Tube: No |
| All figures show nominal value and applicable European Rec | es. Tolerances are according to EN50342 julations. | |

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.