EXIDE TECHNOLOGIES	CUSTOMER D	DATASHEET		ted: 14/02/2022 duct Management nsportation Europe
Central Article Code:	C43009D01-A		Created:	02/09/2005
Local Code:	12N9-4B-1		Modified:	15/12/2020
		Final Outlooi Approval dat	e 15/03/2011	
PERI	FORMANCES		CONTAINER	
Voltage (V):	12 V	Туре:	C43 W	/HITE
C20 (Ah):	9.0 10 h	Hold Down:	B0	
Cranking (A):	85 EN	H.D. Adapter:	No	
Charge:	DRY		COVER	
Technology:	Vented/Flooded	Туре:	Motorbike (B vent	ilati BLACK
Grid:	Low Sb	Polarity:	ETN 1	
Vibration:	Not Defined	Terminals:	M06	
Endurance:	Not Defined	Terminal Adapter:	No	
		SOCI:	No	
		Ventilation:	Moto-B	
STD. DIMENSIONS		-	No	
Length (mm ± 2):	135	Lateral Plug:	No	
Width (mm ± 2):	75		PLUGS	
Height (mm ± 2):	140	Type: 6 x Moto Pl	ug F	RED
Total Weight (kg ± 5%):	3.10	HANDLES		
		Type: None		
			OTUEDO	
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.			OTHERS	

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.