


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C68030D02-A
 Created:
 05/09/2005

 Local Code:
 E60-N30L-A
 Modified:
 15/12/2020







Final Outlook C6802-A Approval date 15/10/2011

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C68	WHITE
C20 (Ah):	30.0	10 h	Hold Down:	B0	
Cranking (A):	300	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	Vented/Flooded		Type:	Motorbike (A ventilati BLACK	
Grid:	Low Sb		Polarity:	ETN 0	
Vibration:	Not Defined		Terminals:	M11	
Endurance:	Not Defined		Terminal Adapter:	No	
	Not Bomileo	•	SOCI:	No	
			Ventilation:	Moto-A	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	185		Lateral Plug:	No	
Width (mm ± 2):	(idth (mm ± 2): 130		PLUGS		
Height (mm ± 2):	170		Type: 6 x Moto Plug RED		RED
Total Weight (kg ± 5%):	8.90			HANDLES	
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.