

and applicable European Regulations.


## **CUSTOMER DATASHEET**


Printed: 09/02/2022


Product Management
Transportation Europe

Central Article Code: B19030C17-A Created: 24/02/2020

Local Code: EA406 Modified: 14/01/2021







Final Outlook B1917-A Approval date 01/02/2022

PERFORMANCES		CONTAINER	
Voltage (V):	12 V	Type:	B19 BLACK
C20 (Ah):	40.0 20 h	Hold Down:	B1
Cranking (A):	350 EN	H.D. Adapter:	No
Charge:	WET		COVER
Technology:	Vented/Flooded	Type:	Double with Integrat BLACK
Grid:	Ca/Ca	Polarity:	ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals:	JIS taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter:	From JIS to EN (Ring adapter)
	(.cc sys.cs@_c/c)	SOCI:	No
		Ventilation:	Central
STD. DIMENSIONS		Filter:	2 Filters
Length (mm ± 2):	187	Lateral Plug:	Standard Left side BLACK shape
Width (mm ± 2):	127		PLUGS
Height (mm ± 2):	220	Type: 1 x Vent S	ealed (JIS) BLACK
Total Weight (kg ± 5%):	9.90		HANDLES
		Type: 1 x Integra	ted BLACK
			OTHERS
		Degassing Tube:	No
All figures show nominal value	es. Tolerances are according to EN50342		