TECHNOLOGIES	CUSTOMER D	Printed: 09/02/2022 Product Management Transportation Europe
Central Article Code:	LB1046C11-D	Created: 24/02/2020
Local Code:	EA472	Modified: 22/01/2021
	207-3 207-3 207-3	
		Final OutlookLB111-DApproval date01/11/2019
PER	FORMANCES	CONTAINER
	FORMANCES	CONTAINER Type: LB1 BLACK
/oltage (V):		
/oltage (V): C20 (Ah):	12 V	Type: LB1 BLACK
/oltage (V): C20 (Ah): Cranking (A):	12 V 47.0 20 h	Type:LB1BLACKHold Down:B13H.D. Adapter:No
/oltage (V): C20 (Ah): Cranking (A): Charge:	12 V 47.0 20 h 450 EN	Type:LB1BLACKHold Down:B13
/oltage (V): C20 (Ah): Cranking (A): Charge: Гесhnology:	12 V 47.0 20 h 450 EN WET	Type: LB1 BLACK Hold Down: B13 H.D. Adapter: No
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid:	12 V 47.0 20 h 450 EN WET Vented/Flooded	Type: LB1 BLACK Hold Down: B13 H.D. Adapter: No COVER Type: Double with Integrat BLACK Polarity: ETN 0 Terminals: EN taper post
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration:	12 V 47.0 20 h 450 EN WET Vented/Flooded Ca/Ca	Type: LB1 BLACK Hold Down: B13 H.D. Adapter: No COVER Type: Double with Integrat BLACK Polarity: ETN 0 Terminals: EN taper post Terminal Adapter: No
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration:	12 V 47.0 20 h 450 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratBLACKPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:No
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance:	12 V 47.0 20 h 450 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:Central
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance:	12 V 47.0 20 h 450 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:CentralFilter:2 FiltersLateral Plug:StandardLeft sideBLACK
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. Length (mm ± 2):	12 V 47.0 20 h 450 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:CentralFilter:2 FiltersLateral Plug:StandardLeft sideBLACK
/oltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2):	12 V 47.0 20 h 450 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratBLACKPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:CentralFilter:2 FiltersLateral Plug:StandardLeteral Plug:StandardLeft sideBLACK
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	12 V 47.0 20 h 450 EN 450 Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with Integrat BLACKPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:CentralFilter:2 FiltersLateral Plug:Standard Left side BLACKPLUGSType:1 x Vent Sealed PSL-OE ha BLACK
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: STD.	12 V 47.0 20 h 450 EN 450 Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type: LB1 BLACK Hold Down: B13 H.D. Adapter: No COVER Type: Double with Integrat Polarity: ETN 0 Terminals: EN taper post Terminal Adapter: No SOCI: No Ventilation: Central Filter: 2 Filters Lateral Plug: Standard Left side BLACK PLUGS Type: 1 x Vent Sealed PSL-OE ha BLACK
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	12 V 47.0 20 h 450 EN 450 Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:CentralFilter:2 FiltersLateral Plug:StandardLeft sideBLACKPLUGSType:1 x Vent Sealed PSL-OE haType:1 x PSL OE IntegratedBLACK
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: STD. Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	12 V 47.0 20 h 450 EN 450 Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E2 (90 cycles@50%)	Type:LB1BLACKHold Down:B13H.D. Adapter:NoCOVERType:Double with IntegratPolarity:ETN 0Terminals:EN taper postTerminal Adapter:NoSOCI:NoVentilation:CentralFilter:2 FiltersLateral Plug:StandardLeft sideBLACKPLUGSType:1 x Vent Sealed PSL-OE ha BLACKHANDLES

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.