


CUSTOMER DATASHEET


Printed: 09/02/2022


Product Management Transportation Europe

L02066C12-C Created: 24/02/2020 Central Article Code:

EA640 Modified: 01/09/2021 Local Code:







Final Outlook L0212-C Approval date 01/11/2019

PERFORMANCES		CONTAINER			
Voltage (V):	12 V	Type:	L02	BLACK	
C20 (Ah):	64.0 20 h	Hold Down:	B13		
Cranking (A):	640 EN	H.D. Adapter:	No		
Charge:	WET		COVER		
Technology:	Vented/Flooded	Type:	Double with Integrat BLACK		
Grid:	Ca/Ca	Polarity:	ETN 0		
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals:	EN taper post		
Endurance:	E2 (90 cycles@50%)	Terminal Adapter:	No		
		SOCI:	No		
		Ventilation:	Central		
STD. DIMENSIONS		Filter:	2 Filters		
Length (mm ± 2):	242	Lateral Plug:	Standard L	eft side BLACK	

Width (mm ± 2): 175 Height (mm ± 2): 190 Total Weight (kg ± 5%): 14.90

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

PLUGS

1 x Vent Sealed PSL-OE ha BLACK Type:

shape

HANDLES

1 x PSL OE Integrated BLACK Type:

OTHERS

Degassing Tube: No