


# **CUSTOMER DATASHEET**


Printed: 09/02/2022


Product Management
Transportation Europe

Central Article Code: D23058C29-A Created: 24/02/2020

Local Code: EA654 Modified: 18/12/2020







Final Outlook D2329-A Approval date 01/04/2021

## **PERFORMANCES**

Voltage (V): 12 V

C20 (Ah): 65.0 20 h Cranking (A): 580 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

# STD. DIMENSIONS

 Length (mm  $\pm$  2):
 230

 Width (mm  $\pm$  2):
 173

 Height (mm  $\pm$  2):
 222

 Total Weight (kg  $\pm$  5%):
 16.80

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Type: D23 BLACK Hold Down: Korean B1

Hold Bown. Rolcan Bi

H.D. Adapter: No

#### COVER

**CONTAINER** 

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central Filter: 2 Filters

Lateral Plug: No

### **PLUGS**

Type: 1 x Vent Sealed (JIS) BLACK

## **HANDLES**

Type: 1 x Integrated BLACK

# **OTHERS**

Degassing Tube: No