


CUSTOMER DATASHEET


Printed: 09/02/2022


Product Management
Transportation Europe

Central Article Code: D31080C42-A Created: 24/02/2020

Local Code: EA954 Modified: 18/12/2020







Final Outlook D3142-A Approval date 15/02/2021

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 95.0 20 h Cranking (A): 800 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h)

Endurance: E1 (180 cycles@25%)

STD. DIMENSIONS

 Length (mm \pm 2):
 306

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 222

 Total Weight (kg \pm 5%):
 23.60

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type: D31 BLACK

Hold Down: Korean B1

H.D. Adapter: No

COVER

Type: Double with Integrat BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

Filter: 2 Filters

Lateral Plug: No

PLUGS

Type: 1 x Vent Sealed (JIS) BLACK

HANDLES

Type: 1 x Integrated BLACK

OTHERS

Degassing Tube: No