


## **CUSTOMER DATASHEET**


Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C47016D02-A
 Created:
 02/09/2005

 Local Code:
 EB10L-A2
 Modified:
 15/12/2020







Final Outlook C4702-A Approval date 15/01/2011

PERFORMANCES		CONTAINER	CONTAINER	
Voltage (V):	12 V	Type: C47 WHITE		
C20 (Ah):	11.0 10 h	Hold Down: B0		
Cranking (A):	130 EN	H.D. Adapter: No		
Charge:	DRY	COVER		
Technology:	Vented/Flooded	Type: Motorbike (A ventilati BLACK	_	
Grid:	Low Sb	Polarity: ETN 0		
Vibration:	Not Defined	Terminals: M08		
Endurance:	Not Defined	Terminal Adapter: No		
	Het Beimed	SOCI: No		
		Ventilation: Moto-A		

## STD. DIMENSIONS

 Length (mm  $\pm$  2):
 135

 Width (mm  $\pm$  2):
 90

 Height (mm  $\pm$  2):
 145

 Total Weight (kg  $\pm$  5%):
 4.10

This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

## **PLUGS**

Type: 6 x Moto Plug RED

No

No

**HANDLES** 

Type: None

Lateral Plug:

Filter:

## **OTHERS**

Degassing Tube: No