


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C47016D01-A
 Created:
 02/09/2005

 Local Code:
 EB10L-B
 Modified:
 15/12/2020







Final Outlook C4701-A Approval date 15/01/2011

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C47	WHITE
C20 (Ah):	11.0	10 h	Hold Down:	B0	
Cranking (A):	130	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	Vented/Flooded		Type:		te (B ventilati BLACK
Grid:	Low Sb		Polarity:	ETN 0	·
Vibration:	Not Defined		Terminals:	M06	
Endurance:	Not Defined	Not Defined		No	
			SOCI:	No	
			Ventilation:	Moto-B	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	135		Lateral Plug:	No	
Width (mm ± 2):	90		PLUGS		
Height (mm ± 2):	145		Type: 6 x Moto F	lug	RED
Total Weight (kg ± 5%): 4.10			HANDLES		
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					