


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

Central Article Code: C45015D01-A Created: 02/09/2005

Local Code: EB12A-A Modified: 15/12/2020







Final Outlook C4501-A Approval date 01/05/2010

PERFORMANCES		
Voltage (V):	12 V	
C20 (Ah):	12.0	10 h
Cranking (A):	165	EN
Charge:	DRY	
Technology:	Vented/Flooded	
Grid:	Low Sb	
Vibration:	Not Defined	
Endurance:	Not Defined	

Type:	C45	WHITE	
Hold Down:	В0		
LIB AT 1			

CONTAINER

H.D. Adapter: No

COVER

Type: Motorbike (A ventilati BLACK

Polarity: ETN 1
Terminals: M06
Terminal Adapter: No
SOCI: No
Ventilation: Moto-A
Filter: No

	STD. DIMENSIONS
Length (mm ± 2):	135

 Width (mm \pm 2):
 80

 Height (mm \pm 2):
 160

 Total Weight (kg \pm 5%):
 4.20

Type: 6 x Moto Plug

No

Type: 6 x Moto Plug RED

HANDLES

OTHERS

This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Type: None

Lateral Plug:

Degassing Tube: No

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.