


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

Central Article Code: C62024D01-A Created: 02/09/2005

Local Code: EB16-B Modified: 15/12/2020







Final Outlook C6201-A Approval date 15/05/2010

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C62	WHITE
C20 (Ah):	19.0	10 h	Hold Down:	B0	
Cranking (A):	190	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	Vented/Flooded		Type:	Motorbike	(B ventilati BLACK
Grid:	Low Sb		Polarity:	ETN 1	
Vibration:	Not Defined		Terminals:	M06	
Endurance:	Not Defined		Terminal Adapter:	No	
	140t Belliled		SOCI:	No	
			Ventilation:	Moto-B	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	175		Lateral Plug:	No	
Width (mm ± 2):	Vidth (mm ± 2): 100		PLUGS		
Height (mm ± 2):	155		Type: 6 x Moto F	Plug	RED
Total Weight (kg ± 5%): 6.00		HANDLES		
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.