TECHNOLOGIES	CUSTOMER [	DATASHEE	Printed: 14/02/2022 Product Management Transportation Europe
Central Article Code:	C63024D01-A		Created: 02/09/2005
Local Code:	EB16CL-B		Modified: 15/12/2020
			Outlook C6301-A aval date 15/05/2010
PERF	0RMANCES		CONTAINER
Voltage (V):	12 V	Туре:	C63 WHITE
C20 (Ah):	12 v 19.0 10 h	Hold Down:	BO
Cranking (A):	190 EN	H.D. Adapter:	No
Charge:	DRY		
Fechnology:	Vented/Flooded		COVER Motorbike (B ventilati BLACK
Grid:	Low Sb	Type: Polarity:	ETN 0
/ibration:	Not Defined	Terminals:	M04
Endurance:	Not Defined	Terminal Adapter:	No
		SOCI:	No
		SOCI: Ventilation:	No Moto-B
	DIMENSIONS		
<b>STD. I</b> _ength (mm ± 2):	175	Ventilation:	Moto-B
<b>STD. I</b> Length (mm ± 2): Width (mm ± 2):	175 100	Ventilation: Filter:	Moto-B No
<b>STD. I</b> Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	175 100 175	Ventilation: Filter:	Moto-B No PLUGS
<b>STD. I</b> Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	175 100	Ventilation: Filter: Lateral Plug:	Moto-B No No PLUGS Iug RED
<b>STD. I</b> Length (mm ± 2):	175 100 175	Ventilation: Filter: Lateral Plug: Type: 6 x Moto Pl	Moto-B No PLUGS
<b>STD. I</b> Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	175 100 175	Ventilation: Filter: Lateral Plug:	Moto-B No No PLUGS Iug RED

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.