


## **CUSTOMER DATASHEET**

Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C65024D02-A
 Created:
 02/09/2005

 Local Code:
 EB18L-A
 Modified:
 15/12/2020







Final Outlook C6502-A Approval date 01/06/2011

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C65	WHITE
C20 (Ah):	18.0	10 h	Hold Down:	B0	
Cranking (A):	190	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	Vented/Flooded		Туре:	Motorbike (A ventilati BLACK	
Grid:	Low Sb		Polarity:	ETN 0	
Vibration:	Not Defined		Terminals:	M07	
Endurance:	Not Defined		Terminal Adapter:	No	
	rtot Bomiou		SOCI:	No	
			Ventilation:	Moto-A	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	180		Lateral Plug:	No	
Width (mm ± 2):			PLUGS		
Height (mm ± 2):	160		Type: 6 x Moto P	lug	RED
Total Weight (kg ± 5%):	6.00		HANDLES		
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					