


CUSTOMER DATASHEET


28/03/2022 Printed:


Product Management Transportation Europe

B19024C18-B Central Article Code: Created: 09/02/2022

14/02/2022 Local Code: EB356 Modified:







Final Outlook B1918-B Approval date 01/02/2022

PERFORMANCES		CONTAINER
Voltage (V):	12 V	Type: B19 BLACK
C20 (Ah):	35.0 20 h	Hold Down: B0
Cranking (A):	240 EN	H.D. Adapter: No
Charge:	WET	COVER
Technology:	Vented/Flooded	Type: Double with Integrat BLACK
Grid:	Ca/Ca	Polarity: ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals: JIS taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter: No
	21 (100 by 0100@2070)	SOCI: No
		Ventilation: Central
STD. DIMENSIONS		Filter: 2 Filters
Length (mm ± 2):	187	Lateral Plug: Standard Left side RED shape
Width (mm ± 2):	127	PLUGS
Height (mm ± 2):	220	Type: 1 x Vent Sealed (JIS) BLACK
Total Weight (kg ± 5%)	8.90	HANDLES
		Type: 1 x Integrated BLACK
		OTHERS
		Degassing Tube: No
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.		342