


## **CUSTOMER DATASHEET**


Printed: 28/03/2022


Product Management
Transportation Europe

 Central Article Code:
 B19024C20-A
 Created:
 09/02/2022

 Local Code:
 EB356A
 Modified:
 14/02/2022







Final Outlook Approval date

B1920-A 01/02/2022

PERFORMANCES		CONTAINER	
Voltage (V):	12 V	Type:	B19 BLACK
C20 (Ah):	35.0 20 h	Hold Down:	Korean B1 Long
Cranking (A):	240 EN	H.D. Adapter:	No
Charge:	WET	COVER	
Technology:	Vented/Flooded	Type:	Double with Integrat BLACK
Grid:	Ca/Ca	Polarity:	ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals:	JIS taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter:	No
	2. (100 0)0.00@2070/	SOCI:	No
		Ventilation:	Central
STD. DIMENSIONS		Filter:	2 Filters
Length (mm ± 2):	187	Lateral Plug:	Standard Left side RED shape
Width (mm ± 2):	127		PLUGS
Height (mm ± 2):	220	Type: 1 x Vent S	ealed (JIS) BLACK
Total Weight (kg ± 5%):	8.90		HANDLES
		Type: 1 x Integra	ted BLACK
			OTHERS
		Degassing Tube:	No
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.			