EXIDE TECHNOLOGIES	CUSTOMER	DATASHEET Printed: 28/03/2022 Product Management Transportation Europe
Central Article Code:	B24033C45-B	Created: 09/02/2022
Local Code:	EB454	Modified: 14/02/2022
		Final Outlook B2445-B Approval date 01/02/2022
PERFORMANCES		CONTAINER
Voltage (V):	12 V	Type: B24 BLACK
C20 (Ah):	45.0 20 h	Hold Down: B0
Cranking (A):	330 EN	H.D. Adapter: No
Charge:	WET	COVER
Technology:	Vented/Flooded	Type: Double with Integrat BLACK
Grid:	Ca/Ca	Polarity: ETN 0
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals: EN taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter: No
		SOCI: No
OTD		Ventilation: Central
Length (mm ± 2):	DIMENSIONS	Filter: 2 Filters Lateral Plug: Standard Left side RED
	237	shape
Lengur (mm ± 2).		·
Width (mm \pm 2):	127	PLUGS
Width (mm ± 2): Height (mm ± 2):	227	PLUGS Type: 1 x Vent Sealed (JIS) BLACK
Width (mm ± 2):		Type: 1 x Vent Sealed (JIS) BLACK
Width (mm ± 2): Height (mm ± 2):	227	Type: 1 x Vent Sealed (JIS) BLACK HANDLES
Width (mm ± 2): Height (mm ± 2):	227	Type: 1 x Vent Sealed (JIS) BLACK HANDLES Type: 1 x Integrated BLACK
Width (mm ± 2): Height (mm ± 2):	227	Type: 1 x Vent Sealed (JIS) BLACK HANDLES

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.