


CUSTOMER DATASHEET


Printed: 28/03/2022


Product Management
Transportation Europe

Central Article Code: B24033C47-C Created: 09/02/2022

Local Code: EB456 Modified: 14/02/2022







Final Outlook
Approval date

B2447-C 01/02/2022

HANDLES

OTHERS

No

BLACK

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	B24	BLACK
C20 (Ah):	45.0	20 h	Hold Down:	B0	
Cranking (A):	330	EN	H.D. Adapter:	No	
Charge:	WET		COVER		
Technology:	Vented/Flooded		Type:	Double with Integrat BLACK	
Grid:	Ca/Ca		Polarity:	ETN 0	
Vibration:	V1 (30Hz+/-2Hz/3g/2h)		Terminals:	JIS taper post	
Endurance:	E1 (180 cycles@25%)		Terminal Adapter:	No	
	21 (100 dydiod@2070)		SOCI:	No	
			Ventilation:	Central	
STD. DIMENSIONS			Filter:	2 Filters	
Length (mm ± 2):	237		Lateral Plug:	Standard shape	Left side RED
Width (mm ± 2):	127		PLUGS		
Height (mm ± 2):	227		Type: 1 x Vent Sealed (JIS) BLACK		
Total Weight (kg ± 5%):	11.40		HANDLES		

All figures show nominal values. Tolerances are according to EN50342

and applicable European Regulations.

Type:

1 x Integrated

Degassing Tube: