


CUSTOMER DATASHEET


Printed: 09/02/2022


Product Management
Transportation Europe

Central Article Code: D20036C12-A Created: 10/05/2018

Local Code: EB504 Modified: 15/06/2018







Final Outlook D2012-A Approval date 01/07/2018

	PERFORMANCES	
Voltage (V):	12 V	
C20 (Ah):	50.0	2

DEDECODMANCES

C20 (Ah): 50.0 20 h Cranking (A): 360 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

 Vibration:
 V1 (30Hz+/-2Hz/3g/2h)

 Endurance:
 E1 (180 cycles@25%)

	COVER	•
H.D. Adapter:	No	

D20

Type: Double with Integrat BLACK

Korean B1

CONTAINER

BLACK

Polarity: ETN 0

Type:

Hold Down:

Terminals: EN taper post

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 2 Filters
Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 200

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 222

 Total Weight (kg \pm 5%):
 13.00

PLUGS

Type: 1 x Vent Sealed (JIS) BLACK

HANDLES

Type: 1 x Integrated BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.