<b>EXIDE</b> TECHNOLOGIES	CUSTOMER	DATASHEET Printed: 09/02/2022 Product Management Transportation Europe
Central Article Code:	D20036C13-A	Created: 10/05/2018
Local Code:	EB505	Modified: 15/06/2018
		171±2 0 171±2 171±2 167±2 175±2
		Final Outlook D2013-A Approval date 01/07/2018
PERF	ORMANCES	CONTAINER
Voltage (V):	12 V	Type: D20 BLACK
C20 (Ah):	50.0 20 h	Hold Down: Korean B1
Cranking (A):	360 EN	H.D. Adapter: No
Charge:	WET	COVER
Technology:	Vented/Flooded	Type: Double with Integrat BLACK
Grid:	Ca/Ca	Polarity: ETN 1
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals: EN taper post
Endurance:	E1 (180 cycles@25%)	Terminal Adapter: No
		SOCI: No
		Ventilation: Central
STD.	DIMENSIONS	Filter: 2 Filters
Length (mm ± 2):	200	Lateral Plug: No
Width (mm ± 2):	173	PLUGS
Height (mm ± 2):	222	Type: 1 x Vent Sealed (JIS) BLACK
Total Weight (kg ± 5%):	13.00	HANDLES
		Type: 1 x Integrated BLACK
		OTHERS
All figures show nominal values and applicable European Regu	s. Tolerances are according to EN50342 llations.	Degassing Tube: No

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.