


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

Central Article Code: C38006D03-A Created: 03/12/2009

Local Code: EB5L-B Modified: 15/12/2020







Final Outlook C3803-A Approval date 15/03/2010

PERFORMANCES				CONTAINER		
Voltage (V):	12 V		Type:	C38	WHITE	
C20 (Ah):	5.0	10 h	Hold Down:	B0		
Cranking (A):	65	EN	H.D. Adapter:	No		
Charge:	DRY			COVER		
Technology:	Vented/Flooded		Type:	Motorbike (B ventilati BLACK		
Grid:	Low Sb		Polarity:	ETN 0		
Vibration:	Not Defined		Terminals:	M06		
Endurance: Not Define		ned	Terminal Adapter:	No		
			SOCI:	No		
			Ventilation:	Moto-B		
STD. DIMENSIONS			Filter:	No		
Length (mm ± 2):	120		Lateral Plug:	No		

 Length (mm \pm 2):
 120

 Width (mm \pm 2):
 60

 Height (mm \pm 2):
 130

 Total Weight (kg \pm 5%):
 2.00

This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

PLUGS

Type: 6 x Moto Plug RED

HANDLES

Type: None

OTHERS

Degassing Tube: No