


CUSTOMER DATASHEET


Printed: 09/02/2022


Product Management Transportation Europe

D23039C26-A Created: 10/05/2018 Central Article Code:

Modified: 31/07/2020 Local Code: EB604







Final Outlook D2326-A Approval date 01/07/2018

PERFORMANCES

Voltage (V): 12 V

C20 (Ah): 60.0 20 h 480 ΕN Cranking (A):

WET Charge:

Vented/Flooded Technology:

Grid: Ca/Ca

Vibration: V1 (30Hz+/-2Hz/3g/2h) Endurance: E1 (180 cycles@25%)

STD. DIMENSIONS

Length (mm ± 2): 230 Width $(mm \pm 2)$: 173 Height (mm ± 2): 222 Total Weight (kg ± 5%): 15.00

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

D23 **BLACK** Type: Korean B1

Hold Down:

H.D. Adapter: No

COVER

Type: Flat/Press integrated BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Central

Filter: 1 Filter at Right

Lateral Plug:

PLUGS

1 x VCL Vent BLACK Type:

HANDLES

1 x Integrated BLACK Type:

OTHERS

Degassing Tube: No