


CUSTOMER DATASHEET


Printed: 09/09/2021


Product Management
Transportation Europe

Central Article Code: C42010D01-A Created: 02/09/2005

Local Code: EB7-A Modified: 15/12/2020







Final Outlook C4201-A Approval date 15/08/2010

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C42	WHITE
C20 (Ah):	8.0	10 h	Hold Down:	В0	
Cranking (A):	85	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	Vented/Flooded		Type:	Motorbike (A ventilati BLACK	
Grid:	Low Sb		Polarity:	ETN 1	·
			Terminals:	M06	
			Terminal Adapter:	No	
			SOCI:	No	
			Ventilation:	ntilation: Moto-A	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	135		Lateral Plug:	No	
Width (mm ± 2): 75		PLUGS			
Height (mm ± 2):	135		Type: 6 x Moto P	lug	RED
			HANDLES		IDLES
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					