CUSTOMER I		DATASHEE			d: 10/02/2022 ct Management portation Europe	
Central Article Code:	L01036C14-B		Creat	-	22/09/2005	
Local Code:	EC440		Modif	fied:	31/07/2020	
	205±C,4		5-2			
		Final Outlook Approval date	L0114-B 01/06/2015			
PERF	ORMANCES		CONTA	INER		
	ORMANCES	Туре:	CONTA	INER BLACK		
/oltage (V):		Type: Hold Down:				
/oltage (V): C20 (Ah):	12 V		L01			
/oltage (V): C20 (Ah): Cranking (A):	12 V 44.0 20 h	Hold Down:	L01 B13 No	BLACK		
Voltage (V): C20 (Ah): Cranking (A): Charge:	12 V 44.0 20 h 360 EN	Hold Down: H.D. Adapter:	L01 B13 No	BLACK ER		
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology:	12 V 44.0 20 h 360 EN WET Vented/Flooded	Hold Down:	L01 B13 No	BLACK	SLACK	
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid:	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca	Hold Down: H.D. Adapter: Type:	L01 B13 No COV	BLACK ER B		
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration:	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h)	Hold Down: H.D. Adapter: Type: Polarity:	L01 B13 No COV NPR ETN 0 EN taper po	BLACK ER B		
/oltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration:	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca	Hold Down: H.D. Adapter: Type: Polarity: Terminals:	L01 B13 No COV NPR ETN 0 EN taper po	BLACK ER B		
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance:	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%)	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation:	L01 B13 No COV NPR ETN 0 EN taper po No No Central	BLACK ER B		
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance: <b>STD. C</b>	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter:	L01 B13 No COV NPR ETN 0 EN taper po No No Central 2 Filters	BLACK ER B	BLACK	
/oltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration: Endurance: <b>STD. C</b>	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%)	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation:	L01 B13 No COV NPR ETN 0 EN taper po No No Central	BLACK ER B	BLACK	
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration: Endurance: <b>STD. E</b> _ength (mm ± 2): Width (mm ± 2):	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS 207 175	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter:	L01 B13 No COV NPR ETN 0 EN taper po No No Central 2 Filters Standard	BLACK ER B ost Right side	BLACK	
/oltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: /ibration: Endurance: <b>STD. I</b> Length (mm ± 2): Vidth (mm ± 2): Height (mm ± 2):	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS 207 175 190	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter:	L01 B13 No COV NPR ETN 0 EN taper po No No Central 2 Filters Standard shape PLUC	BLACK ER B ost Right side	BLACK	
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: <b>STD. I</b> Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS 207 175	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug:	L01 B13 No COV NPR ETN 0 EN taper po No Central 2 Filters Standard shape PLUC Manifold)	BLACK ER Bost Right side GS BLAC	BLACK	
Voltage (V): C20 (Ah): Cranking (A): Charge: Technology: Grid: Vibration: Endurance:	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS 207 175 190	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug:	L01 B13 No COV NPR ETN 0 EN taper po No Central 2 Filters Standard shape PLUC Manifold)	BLACK ER Bost Right side GS BLAC	BLACK	
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: <b>STD. I</b> Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS 207 175 190	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 1 x NPR (	L01 B13 No COV NPR ETN 0 EN taper po No Central 2 Filters Standard shape PLUC Manifold)	BLACK ER Bost Right side GS BLAC LES BLAC	BLACK	
Voltage (V): C20 (Ah): Cranking (A): Charge: Fechnology: Grid: Vibration: Endurance: <b>STD. I</b> Length (mm ± 2): Width (mm ± 2): Height (mm ± 2):	12 V 44.0 20 h 360 EN WET Vented/Flooded Ca/Ca V1 (30Hz+/-2Hz/3g/2h) E1 (180 cycles@25%) DIMENSIONS 207 175 190	Hold Down: H.D. Adapter: Type: Polarity: Terminals: Terminal Adapter: SOCI: Ventilation: Filter: Lateral Plug: Type: 1 x NPR (	L01 B13 No COV NPR ETN 0 EN taper po No Central 2 Filters Standard shape PLUC Manifold) HAND Thin)	BLACK ER Bost Right side GS BLAC LES BLAC	BLACK	

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.