


## **CUSTOMER DATASHEET**


Printed: 10/02/2022
Product Management


Transportation Europe

Central Article Code: G31100C10-A Created: 12/06/2012

Local Code: EG110B Modified: 18/09/2019







Final Outlook G3110-A Approval date 15/09/2019

	31				$\frown$		N	14	. N			C
- 1	7	=1	ĸ	Г,	u	К	IV	1/4	١N	ıL	, C	ĸ

Voltage (V): 12 V

C20 (Ah): 110.0 20 h

Cranking (A): 1000 SAE 7.2 v 30

Sec.

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V2 (30Hz+/-2Hz/6g/2h)

Endurance: E2 (90 cycles@50%)

## CONTAINER

Type: G31 BLACK

Hold Down: B0 H.D. Adapter: No

## COVER

Type: Double with Integrat BLACK

Polarity: ETN 9

Terminals: SAE A taper post

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: No

Lateral Plug: No

## **STD. DIMENSIONS**

 Length (mm  $\pm$  2):
 330

 Width (mm  $\pm$  2):
 173

 Height (mm  $\pm$  2):
 240

 Total Weight (kg  $\pm$  5%):
 27.40

Type: 1 x Vent

BLACK

HANDLES

Type: 1 x Integrated BLACK

**OTHERS** 

**PLUGS** 

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.