


CUSTOMER DATASHEET


Printed: 10/02/2022


Product Management
Transportation Europe

Central Article Code: D06120C01-A Created: 21/05/2014

Local Code: EG2253 Modified: 11/01/2021







Final Outlook D0601-A Approval date 01/10/2005

			0			A 1	NT.	_	•
$\boldsymbol{\nu}$	-1	~ -	-()	K	W	ΔІ	M	_	•

Voltage (V): 12 V

C20 (Ah): 225.0 20 h Cranking (A): 1200 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V2 (30Hz+/-2Hz/6g/2h)

Endurance: E2 (90 cycles@50%)

CONTAINER

Type: D06 BLACK Hold Down: B0

H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 518

 Width (mm \pm 2):
 274

 Height (mm \pm 2):
 240

 Total Weight (kg \pm 5%):
 54.90

Type: 2 x R

PLUGS

Type: 6 x M27 BLACK

HANDLES

Type: 2 x Rope (Rigid holder) BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.