


CUSTOMER DATASHEET


Printed: 09/02/2022


Product Management
Transportation Europe

Central Article Code: C76008A03-A Created: 16/06/2011

Local Code: EK143 Modified: 14/03/2019







Final Outlook C7603-A Approval date 15/06/2015

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C76	BLACK
C20 (Ah):	14.0	20 h	Hold Down:	B0	
Cranking (A):	80	Not applicable	H.D. Adapter:	No	
Charge: CHARGED		COVER			
Technology:	AGM		Type:	Flat/Screw	BLACK
Grid:	Ca/Ca		Polarity:	ETN 3	
Vibration:	V3 (30Hz+/-2Hz/6g/20h)		Terminals:	Screwed/Lug	
Endurance:	300 cycles@75%		Terminal Adapter:	No	
	ooo oyoloo	366,1070	SOCI:	No	
			Ventilation:	Independent	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	150		Lateral Plug:	No	
Width (mm ± 2): 100		PLUGS			
Height (mm ± 2):	100		Type: 6 x Valve+	Cover	BLACK
Total Weight (kg ± 5%	6): 4.20		HANDLES		
			Type: None		
			OTHERS		
			Degassing Tube:	No	
All figures show nominal va and applicable European R		e according to EN50342			