


### **CUSTOMER DATASHEET**


Printed: 09/02/2022


Product Management
Transportation Europe

Central Article Code: L04079A14-D Created: 13/05/2013

Local Code: EK800 Modified: 31/07/2020







Final Outlook L0414-D Approval date 15/10/2013

	PERI ORMANCE	_3	
Voltage (V):	12 V		
C20 (Ah):	80.0	20 h	
Cranking (A):	800	EN	
Charge:	CHARGED	1	

PERFORMANCES

Technology: AGM
Grid: Ca/Ca

Length (mm ± 2):

Vibration: Manufactured Specific Endurance: VDA Requirement

# COVER

L04

B13

No

Type: Double with Integrat BLACK

**CONTAINER** 

**BLACK** 

Polarity: ETN 0
Terminals: EN taper post

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 2 Filters

Type:

Hold Down: H.D. Adapter:

Lateral Plug: Standard Right side BLACK shape

## 315 Lateral Plug:

Width (mm  $\pm$  2): 175 Height (mm  $\pm$  2): 190 Total Weight (kg  $\pm$  5%): 23.10

STD. DIMENSIONS

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

#### **PLUGS**

Type: 1 x Vent Sealed (Valve) BLACK

#### HANDLES

Type: 2 x Integrated BLACK

#### **OTHERS**

Degassing Tube: No