


## **CUSTOMER DATASHEET**


Printed: 09/02/2022


**Product Management** Transportation Europe

L01050C18-C Created: 08/03/2021 Central Article Code:

EL550 Modified: 22/03/2021 Local Code:







**Final Outlook** L0118-C Approval date 01/11/2019

PERFURIMANCES			
Voltage (V):	12 V		
C20 (Ah):	55.0	20 h	
Cranking (A):	540	EN	
Charge:	WET		
Technology:	Vented/Flo	Vented/Flooded	
Grid:	Ca/Ca		
Vibration:	V1 (30Hz+	V1 (30Hz+/-2Hz/3g/2h)	
Endurance:	EN-EFB Requirement		

**STD. DIMENSIONS** 

Length (mm ± 2):

DEDECODMANCES

CONTAINER					
Type:	L01	BLACK			
Hold Down:	B13				
H.D. Adapter:	No				
COVER					
Type: Double with Integrat BLACK					

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central 2 Filters Filter:

**BLACK** 

## 207 Lateral Plug: Standard Left side shape

Degassing Tube:

Width (mm ± 2):	175	PLUGS
Height (mm ± 2): Total Weight (kg ± 5%):	190 14.10	Type: 1 x Vent Sealed PSL-OE ha BLACK
Total Weight (kg ± 570).	14.10	HANDLES

		HANDLES		
	Type:	1 x PSL OE Integrated	BLACK	
OTHERS				

No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.