


CUSTOMER DATASHEET


Printed: 14/02/2022

Product Management
Transportation Europe

Central Article Code: C50019L04-A Created: 29/09/2016

Local Code: ELT9B Modified: 13/12/2016







Final Outlook C5004-A Approval date 15/11/2016

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C50	BLACK
C20 (Ah):	3.0	10 h	Hold Down:	B0	
Cranking (A):	190	25° test	H.D. Adapter:	No	
Charge:	CHARGED		COVER		
Technology:	Li-ion		Type:	Motorbike	e (central ve ORANGE (Li-ion
Grid:	LiFePO4		Polarity:	ETN 1	
Vibration:	3 axis acc. UN38.3 req.		Terminals:	M12	
Endurance:	•		Terminal Adapter:	No	
	20000 41 0	.0,0 202	SOCI:	Digital SC	OCI
			Ventilation:	Central	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	150		Lateral Plug:	No	
Width (mm ± 2):	65		PLUGS		
Height (mm ± 2):	95		Type: 1 x Not de	fined	NOT SIGNIFICANT
Total Weight (kg ± 5%):	0.70		HANDLES		
			Type: None		
			OTHERS		
			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.