


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

Central Article Code: G34075M01-A Created: 06/09/2005

Local Code: EP450 Modified: 28/10/2020







Final Outlook G3401-A Approval date 01/11/2010

PERFORMANCES			
Voltage (V):	12 V		
C20 (Ah):	50.0	20 h	
Cranking (A):	750	EN	
Charge:	CHARGE	CHARGED	
Technology:	Orbital		
Grid:	Pb-Sn		
Vibration:	V3+ (30Hz+/-2Hz/6g/60h)		
Endurance:	500 cycles@75%		

Type:	G34	BLACK	
Hold Down:	B7		
H.D. Adapter:	No		

CONTAINER

COVER Type: Maxxima/Orbital BLUE LIGHT Polarity: ETN 1

V3+ (30Hz+/-2Hz/6g/60h) Terminals: SAE M 3/8"- 5/16" taper&stud

Terminal Adapter: No
SOCI: No
Ventilation: Central
Filter: 2 Filters
Lateral Plug: No

STD. DIMENSIONS

 Length (mm ± 2):
 260

 Width (mm ± 2):
 173

 Height (mm ± 2):
 206

 Total Weight (kg ± 5%):
 18.60

PLUGS

Type: 6 x Valve+Cover BLACK

HANDLES

Type: 2 x Integrated BLACK

OTHERS

Degassing Tube: No

3/8-5/16 nuts in plastic bag

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.