| EXIDE | CUSTOMER I | DATASHEET Printed: 14/02/2022 Product Management Transportation Europe |
|--|---|--|
| Central Article Code: | L03075A26-K | Created: 04/12/2017 |
| Local Code: | EP600 | Modified: 11/11/2021 |
| | | |
| | | Final Outlook L0326-K Approval date 01/12/2017 |
| PERI | FORMANCES | CONTAINER |
| Voltage (V): C20 (Ah): Cranking (A): | 12 V 70.0 20 h 760 EN | Type:L03BLACKHold Down:B13H.D. Adapter:No |
| Charge: | CHARGED | COVER |
| Technology: | AGM | Type: Double with Integrat BLACK |
| Grid: | Ca/Ca | Polarity: ETN 0 |
| Vibration: | Manufactured Specific | Terminals: EN taper post |
| Endurance: | VDA Requirement | Terminal Adapter: No |
| | , | SOCI: No |
| | | Ventilation: Central |
| STD. DIMENSIONS | | Filter: 2 Filters |
| Length (mm ± 2): | 278 | Lateral Plug: Standard Left side BLACK shape |
| Width (mm ± 2): | 175 | PLUGS |
| Height (mm ± 2): | 190 | Type: 1 x Vent Sealed (Valve) BLACK |
| Total Weight (kg ± 5%): 20.60 | | HANDLES |
| | | |
| | | |
| | | OTHERS |
| All figures show nominal value and applicable European Regu | s. Tolerances are according to EN50342 alations. | Degassing Tube: No |

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.