


CUSTOMER DATASHEET


Printed: 14/02/2022

Product Management
Transportation Europe

Central Article Code: D03085W12-A Created: 29/09/2010

Local Code: ER650 Modified: 31/07/2020





A	

Final Outlook D0312-A Approval date 15/01/2011

	_	\sim			-
u		. ()	' N/I /\	NI ('	_
	_1\1	\mathbf{v}	MA		

Voltage (V): 12 V

C20 (Ah): 142.0 20 h Cranking (A): 850 EN

Charge: WET

Technology: Vented/Flooded

Grid: Hybrid

Vibration: V2 (30Hz+/-2Hz/6g/2h)

Endurance: 300 cycles@40%

CONTAINER

Type: D03 BLACK Hold Down: B0

H.D. Adapter: No

COVER

Type: Flat/Press BLUE LIGHT

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No

SOCI: Black SOCI with one ball

Ventilation: Central

Filter: 1 Filter at Right

Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 349

 Width (mm \pm 2):
 175

 Height (mm \pm 2):
 285

 Total Weight (kg \pm 5%):
 35.10

Type: 1 x VCL Vent

BLUE LIGHT

HANDLES

PLUGS

Type: 2 x Rigid BLACK

OTHERS

Degassing Tube: Tube+Valve

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.