	CUSTOMER DATASHEET		Printed: 14/02/2022 Product Management Transportation Europe		
Central Article Code:	D07076G02-A		Created:	06/09/2005	
Local Code:	ES1200		Modified:	20/03/2019	
100		Final Outlook Approval date	D0702-A 01/10/2005		
	254*2	<u>+</u>			
PERFORMANCES			CONTAINER		
Voltage (V):	12 V	Type: D	07 BL	ACK	
C20 (Ah):	110.0 20 h	Hold Down: B			
Cranking (A):	0 EN	H.D. Adapter: N	0		
Charge:	CHARGED		COVER		
Technology:	GEL	Type: F	lat/Screw	BLACK	
Grid:	Ca/Ca	Polarity: E	TN 2		
Vibration:	V3 (30Hz+/-2Hz/6g/20h)	Terminals: E	N taper post		
Endurance:	200 cycles@100%	Terminal Adapter: N			
		SOCI: N			
			ndependent		
	DIMENSIONS	Filter: N			
$-ength (mm \pm 2):$	286	Lateral Plug: N	0		
Width (mm ± 2):	269		PLUGS		
Height (mm \pm 2):	230	Type: 6 x M18 Valv	e G	REY MEDIUM	
Total Weight (kg ± 5%):	37.30	37.50 HANDLES			
		Type: 2 x Rope (Rid	Type: 2 x Rope (Rigid holder) BLACK		
			OTHERS		
		Degessing Tuber			
		Degassing Tube: Gel	No		
All figures show nominal values and applicable European Regu	s. Tolerances are according to EN50342 lations.				

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.