


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management Transportation Europe

D03075G05-A Created: 05/09/2005 Central Article Code:

Modified: 20/03/2019 Local Code: ES1300







Final Outlook D0305-A Approval date 15/06/2013

CONTAINER

P	F	R	F		R	M	A	N	C	F	Ç
	_			u		IVI		14	v	_	L

Voltage (V): 12 V

C20 (Ah): 120.0 20 h ΕN Cranking (A):

CHARGED Charge:

Technology: GEL Grid:

Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 400 cycles@100%

D03 **BLACK** Type: B0 Hold Down:

H.D. Adapter: No

COVER

Type: Flat/Press BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 349 Width $(mm \pm 2)$: 175 Height (mm ± 2): 285 Total Weight (kg ± 5%): 37.50

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

PLUGS

6 x M18 Valve **GREY MEDIUM** Type:

HANDLES

2 x Rigid BLACK Type:

OTHERS

Degassing Tube: No