


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

Central Article Code: LB1028G19-A Created: 06/09/2005

Local Code: ES450 Modified: 20/03/2019







Final Outlook LB119-A Approval date 15/08/2011

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	LB1	BLACK
C20 (Ah):	40.0	20 h	Hold Down:	B4	
Cranking (A):	0	EN	H.D. Adapter:	No	
Charge:	CHARGED		COVER		
Technology:	GEL		Type:	DIN	BLACK
Grid:	Ca/Ca		Polarity:	ETN 0	
Vibration:	V3 (30Hz+/-2Hz/6g/20h)		Terminals:	EN full Ford lug	
Endurance:	200 cycles@100%		Terminal Adapter:	No	
			SOCI:	No	

Ventilation:

Lateral Plug:

Filter:

Type:

STD. DIMENSIONS

 Length (mm \pm 2):
 207

 Width (mm \pm 2):
 175

 Height (mm \pm 2):
 175

 Total Weight (kg \pm 5%):
 14.20

PLUGS

No

No

Type: 6 x M18 Valve GREY MEDIUM

Independent

HANDLES

None

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.