

CUSTOMER DATASHEET

Printed: 14/02/2022

Product Management Transportation Europe

Central Article Code:

D02046G12-A

Created:


05/09/2005


Local Code:


ES950

Modified:

20/03/2019







D0212-A Final Outlook Approval date 01/10/2005

PERFORMANCES

0

Voltage (V): 12 V

C20 (Ah): 85.0

20 h ΕN

Cranking (A): **CHARGED** Charge:

Technology: GEL

Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: 300 cycles@100%

D02 Type:

B0 Hold Down: H.D. Adapter: No

COVER

CONTAINER

BLACK

Type: Flat/Screw BLACK

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 349 Width $(mm \pm 2)$: 175

Height (mm ± 2): 235

Total Weight (kg ± 5%): 28.20 **PLUGS**

6 x M18 Valve **GREY MEDIUM** Type:

HANDLES

2 x Rigid BLACK Type:

OTHERS

Degassing Tube:

No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.