


CUSTOMER DATASHEET


Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C54013F02-A
 Created:
 26/10/2006

 Local Code:
 ET12A-BS
 Modified:
 15/12/2020







Final Outlook C5402-A Approval date 01/12/2009

PERFORMANCES			CONTAINER				
Voltage (V):	12 V		Type:		C54	BLACK	
C20 (Ah):	10.0	10 h	Hold Do	own:	B0		
Cranking (A):	130	EN	H.D. Ad	lapter:	No		
Charge:	DRY		COVER				
Technology:	AGM		Type:		Motorbike	e (independ BLACK	
Grid:	Ca/Ca		Polarity:		ETN 1		
Vibration:	Not Defined		Terminals:		M04		
Endurance:	Not Defined		Termina	l Adapter:	No		
			SOCI:		No		
			Ventilati	on:	Sealed		
STD. DIMENSIONS			Filter:		No		
Length (mm ± 2):	150		Lateral I	Plug:	No		
Width (mm ± 2):	90		PLUGS				
Height (mm ± 2):	105		Type:	1 x Vent		BLACK	
Total Weight (kg ± 5%):	3.40				HANDLES		
			Type:	None			
			OTHERS				
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degass	ing Tube:	No		
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.							

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.