


CUSTOMER DATASHEET

Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C34003F01-A
 Created:
 26/10/2006

 Local Code:
 ETR4A-BS
 Modified:
 15/12/2020







Final Outlook C3401-A Approval date 01/12/2009

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C34	BLACK
C20 (Ah):	2.3	10 h	Hold Down:	B0	
Cranking (A):	35	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	AGM		Туре:	Motorbik	e (independ BLACK
Grid:	Ca/Ca		Polarity:	ETN 4	
Vibration:	Not Defined		Terminals:	M14	
Endurance:	Not Defined		Terminal Adapter:	No	
	Not Boiling	•	SOCI:	No	
			Ventilation:	Sealed	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	115		Lateral Plug:	No	
Width (mm ± 2):	50		PLUGS		
Height (mm ± 2):	85		Type: 1 x Vent		BLACK
Total Weight (kg ± 5%): 1.00		HANDLES		
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal va and applicable European Re		according to EN50342			