


## **CUSTOMER DATASHEET**

Printed: 14/02/2022


Product Management
Transportation Europe

 Central Article Code:
 C37008F01-A
 Created:
 26/10/2006

 Local Code:
 ETX7L-BS
 Modified:
 15/12/2020







Final Outlook C3701-A Approval date 01/12/2009

PERFORMANCES			CONTAINER		
Voltage (V):	12 V		Type:	C37	BLACK
C20 (Ah):	6.0	10 h	Hold Down:	B0	
Cranking (A):	100	EN	H.D. Adapter:	No	
Charge:	DRY		COVER		
Technology:	AGM		Type:	Motorbik	e (independ BLACK
Grid:	Ca/Ca		Polarity:	ETN 0	
Vibration:	Not Defined		Terminals:	M04	
Endurance:	Not Defined		Terminal Adapter:	No	
			SOCI:	No	
			Ventilation:	Sealed	
STD. DIMENSIONS			Filter:	No	
Length (mm ± 2):	115		Lateral Plug:	No	
Width (mm ± 2):	70		PLUGS		
Height (mm ± 2):	130		Type: 1 x Vent		BLACK
Total Weight (kg ± 5%	: 2.20	HANDLES			
			Type: None		
			OTHERS		
This is a dry battery supplied with bottles of sulphuric acid. Sale of acid to end users is forbidden by Eu.Reg.1148/2019. Dry batteries must be filled with acid before delivery to end users			Degassing Tube:	No	
All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.					