


CUSTOMER DATASHEET


Printed: 14/02/2022

Product Management Transportation Europe

M08130S01-A Created: 07/09/2005 Central Article Code:

Modified: 04/03/2014 Local Code: EU260-6





4	

Final Outlook M0801-A 01/05/2011 Approval date

PERFORMANCES

Voltage (V): 6 V

C20 (Ah): 260.0 20 h 1300 ΕN Cranking (A):

WET Charge:

Vented/Flooded Technology:

Grid: Low Sb

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: E2 (90 cycles@50%)

CONTAINER

M08 **BLACK** Type:

Hold Down: B0 H.D. Adapter: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 345 Width $(mm \pm 2)$: 172 Height (mm ± 2): 286 Total Weight (kg ± 5%): 39.10

3 x M27(STE)

GREY MEDIUM Type:

HANDLES

PLUGS

2 x Rigid **BLACK** Type:

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.