


## **CUSTOMER DATASHEET**


Printed: 17/09/2019


Product Management
Transportation Europe

Central Article Code: B19030C03-A Created: 01/09/2005


Local Code: TA386 Modified: 05/09/2018







Ring Adaptors



Final Outlook B1903-A Approval date 15/12/2013

Voltage (V):	12 V	
C20 (Ah):	38.0	20 h
Cranking (A):	300	EN
Charge:	WET	

**PERFORMANCES** 

Technology: Vented/Flooded

Grid: Ca/Ca

Type:	B19	GREY DARK

Hold Down: B1 H.D. Adapter: No

## COVER

**PLUGS** 

**CONTAINER** 

Type: Double with Inte GREY DARK

Polarity: ETN 0

Terminals: JIS taper post

Terminal Adapter: From JIS to EN (Ring adapter)

SOCI: No
Ventilation: Central
Filter: 2 Filters
Lateral Pluq: No

1 x Vent Seale

STD. DIMENSIONS Lateral Plug:

Length (mm ± 2):	187
Width (mm ± 2):	127
Height (mm ± 2):	220
Total Weight (kg ± 5%):	9.90

Type: 1 x Integrated GRE

GREY DARK

**GREY DARK** 

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Type: