


CUSTOMER DATASHEET

Printed: 11/02/2022


Product Management
Transportation Europe


Central Article Code: B19024C04-A Created: 01/09/2005

Local Code: TB356 Modified: 10/12/2021



Final Outlook B1904-A Approval date 15/03/2019





PI	ERFORMANCES		CONTAIN	IER
Voltage (V):	12 V	Type:	B19	BLACK
C20 (Ah):	35.0 20 h	Hold Down:	B0	
Cranking (A):	240 EN	H.D. Adapter:	No	
Charge:	WET	COVER		
Technology:	Vented/Flooded	Type:	Flat/Screw	BLACK
Grid:	Ca/Ca	Polarity:	ETN 0	
Vibration:	V1 (30Hz+/-2Hz/3g/2h)	Terminals:	JIS taper pos	t
Endurance:	E1 (180 cycles@25%)	Terminal Adapter:	No	
		SOCI:	No	
		Ventilation:	Independent	
STD. DIMENSIONS Filter:		No		

		Ventilation:	Independent		
STD. D	IMENSIONS	Filter:	No		
Length (mm ± 2):	187	Lateral Plug:	No		
Width (mm ± 2):	127		PLUGS		
Height (mm ± 2): Total Weight (kg ± 5%):	220 8.90	Type: 6 x N	118	BLACK	
Total Weight (kg ± 370).	0.30		HANDLES		
			<u> </u>		

HANDLES

Type: None

OTHERS

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

Degassing Tube: No