




Central Article Code: B19024C01-A
 Local Code: TB356A

Created: 04/08/2005
 Modified: 01/06/2020



Final Outlook	B1901-A
Approval date	15/12/2019



PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	35.0 20 h
Cranking (A):	240 EN
Charge:	WET
Technology:	Vented/Flooded
Grid:	Ca/Ca
Vibration:	V1 (30Hz+/-2Hz/3g/2h)
Endurance:	E1 (180 cycles@25%)

STD. DIMENSIONS

Length (mm ± 2):	187
Width (mm ± 2):	127
Height (mm ± 2):	220
Total Weight (kg ± 5%):	8.90

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

CONTAINER

Type:	B19	BLACK
Hold Down:	Korean B1 Long	
H.D. Adapter:	No	

COVER

Type:	Flat/Screw	BLACK
Polarity:	ETN 0	
Terminals:	JIS taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Independent	
Filter:	No	
Lateral Plug:	No	

PLUGS

Type:	6 x M18	BLACK
-------	---------	-------

HANDLES

Type:	None
-------	------

OTHERS

Degassing Tube:	No
-----------------	----