


## **CUSTOMER DATASHEET**

Printed: 11/02/2022


Product Management
Transportation Europe


Central Article Code: B19024C05-A Created: 01/09/2005

Local Code: TB357 Modified: 01/06/2020



Final Outlook B1905-A Approval date 15/03/2019





	PERFORMANCES
Voltage (V):	12 V

C20 (Ah): 35.0 20 h Cranking (A): 240 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

 Vibration:
 V1 (30Hz+/-2Hz/3g/2h)

 Endurance:
 E1 (180 cycles@25%)

## В0

**CONTAINER** 

**BLACK** 

Hold Down: B0 H.D. Adapter: No

Type:

# STD. DIMENSIONS

 Length (mm  $\pm$  2):
 187

 Width (mm  $\pm$  2):
 127

 Height (mm  $\pm$  2):
 220

 Total Weight (kg  $\pm$  5%):
 8.90

#### COVER

Type: Flat/Screw BLACK

B19

Polarity: ETN 1

Terminals: JIS taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

#### PLUGS

Type: 6 x M18 BLACK

**HANDLES** 

Type: None

### **OTHERS**

No

Degassing Tube:

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.