


Central Article Code: D23039C26-A

Created: 10/05/2018

Local Code: TB604

Modified: 31/07/2020



Final Outlook D2326-A  
Approval date 01/07/2018

## PERFORMANCES

Voltage (V):	12 V
C20 (Ah):	60.0 20 h
Cranking (A):	480 EN
Charge:	WET
Technology:	Vented/Flooded
Grid:	Ca/Ca
Vibration:	V1 (30Hz+/-2Hz/3g/2h)
Endurance:	E1 (180 cycles@25%)

## STD. DIMENSIONS

Length (mm ± 2):	230
Width (mm ± 2):	173
Height (mm ± 2):	222
Total Weight (kg ± 5%):	15.00

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

## CONTAINER

Type:	D23	BLACK
Hold Down:	Korean B1	
H.D. Adapter:	No	

## COVER

Type:	Flat/Press integrated	BLACK
Polarity:	ETN 0	
Terminals:	EN taper post	
Terminal Adapter:	No	
SOCI:	No	
Ventilation:	Central	
Filter:	1 Filter at Right	
Lateral Plug:	No	

## PLUGS

Type:	1 x VCL Vent	BLACK
-------	--------------	-------

## HANDLES

Type:	1 x Integrated	BLACK
-------	----------------	-------

## OTHERS

Degassing Tube:	No
-----------------	----