


CUSTOMER DATASHEET


Printed: 11/02/2022


Product Management Transportation Europe

D06080G09-A Created: 26/10/2016 Central Article Code:

TD2103T Modified: 22/03/2021 Local Code:







Final Outlook D0609-A Approval date 15/06/2013

	31				\frown		N	14	. N			C
- 1	7	=1	ĸ	Г,	u	К	IV	1/4	١N	ıL	, C	ĸ

Voltage (V): 12 V

C20 (Ah): 210.0 20 h 800 ΕN Cranking (A):

CHARGED Charge:

Technology: GEL Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: Manufactured Specific

CONTAINER

D06 **BLACK** Type: B0 Hold Down: No

COVER

Type: Flat/Screw BLACK

Polarity: ETN 3

H.D. Adapter:

Terminals: EN taper post

Terminal Adapter: No SOCI:

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 518 Width $(mm \pm 2)$: 274 Height (mm ± 2): 240 Total Weight (kg ± 5%): 66.00

PLUGS

6 x M18 Valve **GREY MEDIUM** Type:

HANDLES

2 x Rope (Rigid holder) BLACK Type:

OTHERS

Degassing Tube: No

Gel

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.