


## **CUSTOMER DATASHEET**


Printed: 11/02/2022


Product Management
Transportation Europe

Central Article Code: D06130C17-A Created: 16/05/2012

Local Code: TF2353 Modified: 31/07/2020







Final Outlook D0617-A Approval date 15/05/2012

	_			$\overline{}$							_	_
_	_	ĸ	-		R	w	ΙД	N	и	-51	_	•
	_			_			_	v v		_	_	•

Voltage (V): 12 V

C20 (Ah): 235.0 20 h Cranking (A): 1300 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: E3 (144 cycles@50%)

# CONTAINER

Type: D06 GREY MEDIUM Hold Down: B0

H.D. Adapter: No

## **COVER**

Type: Flat/Press GREY MEDIUM

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Central

Filter: 1 Filter per Vent

Lateral Plug: No

## **STD. DIMENSIONS**

 Length (mm  $\pm$  2):
 518

 Width (mm  $\pm$  2):
 274

 Height (mm  $\pm$  2):
 240

 Total Weight (kg  $\pm$  5%):
 55.60

#### **PLUGS**

Type: 2 x VCL Vent GREY MEDIUM

#### **HANDLES**

Type: 2 x Rope (Rigid holder) BLACK

#### **OTHERS**

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342

and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.