EXIDE TECHNOLOGIES	CUSTOMER I	Printed: 11/02/2022 Product Management Transportation Europe
Central Article Code:	D02072C01-A	Created: 30/10/2018
Local Code:	TG1100	Modified: 31/07/2020
PER	FORMANCES	Final Outlook D0201-A Approval date 01/10/2005
Voltage (V):	12 V	Type:D02BLACKHold Down:B0
C20 (Ah):	110.0 20 h	
Cranking (A):	720 EN	· · · · · · · · · · · · · · · · · · ·
Charge:	WET	COVER
Technology:	Vented/Flooded	Type: Flat/Press BLACK
Grid:	Ca/Ca	Polarity: ETN 0
Vibration:	V2 (30Hz+/-2Hz/6g/2h)	Terminals: EN taper post
Endurance:	E2 (90 cycles@50%)	Terminal Adapter: No SOCI: No
סדס	DIMENSIONS	Ventilation: Independent Filter: No
Length (mm ± 2):	349	Lateral Plug: No
Width (mm \pm 2):	175	
Height (mm \pm 2):	235	PLUGS
Total Weight (kg \pm 5%):		Type: 2 x Vent BLACK
· • • • • • • • • • • • • • • • • • • •	20.70	HANDLES
		Type: 2 x Rigid BLACK
		OTHERS
		Degassing Tube: No
All figures show nominal valu and applicable European Reg	es. Tolerances are according to EN50342 gulations.	

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.