


CUSTOMER DATASHEET


Printed: 11/02/2022 **Product Management**


Transportation Europe

G31100C10-A 12/06/2012 Central Article Code: Created:

TG110B 18/09/2019 Local Code: Modified:







Final Outlook Approval date 15/09/2019

	7			N A	A	N		_	c
	RF	u	ĸ	IVI	А	N	u	⊏;	č

Voltage (V): 12 V

C20 (Ah): 110.0 20 h

SAE 7.2 v 30 1000 Cranking (A):

Sec.

WET Charge:

Vented/Flooded Technology:

Grid: Ca/Ca

Vibration: V2 (30Hz+/-2Hz/6g/2h)

Endurance: E2 (90 cycles@50%)

CONTAINER

G31 **BLACK** Type:

Hold Down: B0 H.D. Adapter: No

COVER

Type: Double with Integrat BLACK

Polarity: ETN 9

Terminals: SAE A taper post

Terminal Adapter: SOCI: No Ventilation: Central Filter: No Lateral Plug: No

STD. DIMENSIONS

Length (mm ± 2): 330 Width $(mm \pm 2)$: 173 Height (mm ± 2): 240 Total Weight (kg ± 5%):

27.40

Type: 1 x Vent BLACK

HANDLES

Type: 1 x Integrated **BLACK**

OTHERS

PLUGS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.